

Southern Fire Safety

Powder Fire Extinguishers



EPCE1



EPCE4



EPCE6

- Polyester external coating adds extra protection to withstand extreme temperatures, dirty environments and UV degradation.
- Pressure gauge provides instant check of extinguisher's pressure status. This pressure gauge is approved by EN3.
- High grade brass head assembly ensures reliability and optimizes efficiency.
- High quality application hose and nozzle.
- Stored pressure, Nitrogen as propellant gas.
- Working pressure(20jæ): 14 bar.
- Test pressure: 27 bar.
- Extinguishing Agent: ABC Dry Chemical Powder.

CERTIFICATE



Model	EPCE1	EPCE2	EPCE4	EPCE6	EPCE9
Capacity(KG)	1	2	4	6	9
Discharge Time(sec)	9	10	12	15	18
Range(M)	3-4.5	3.5-5	5-6	5-6	5-6
Fire Rating	8A/55B	13A/89B	21A/114B	27A/183B	43A/233B
Height(mm)	350	400	500	525	610
Width(mm)	130	140	210	220	230
Diameter(mm)	85	110	140	162	184
Working Temperature	-30jæ to 60jæ				
Full Weight(kg)	2.2	3.8	7.2	9.9	14.5
Bracket	Vehicle Bracket		Wall Bracket		