

Southern Fire Safety AFFF Foam Fire Extinguishers



EFCE1



EFCE6



EWCE9

- Lining machine & Lining Powder imported from U.K. provide high quality internal lining against corrosion.
- Polyester external coating adds extra protection to withstand extreme temperatures, dirty environments and UV degradation.
- Pressure gauge provides instant check of extinguisher's pressure status. This pressure gauge is approved by EN3.
- High grade brass head assembly ensures reliability and optimizes efficiency.
- High quality application hose and nozzle.
- Stored pressure, Nitrogen as propellant gas.
- Working pressure(20°C): 14 bar.
- Test pressure: 27 bar.
- Extinguishing Agent: 6% AFFF Foam. Or Water.

CERTIFICATE



Model	EFCE1	EFCE2	EFCE6	EFCE9	EWCE6	EWCE9
Capacity(L)	1	2	6	9	6	9
Discharge Time(sec)	12	20	30	40	40	60
Range(M)	3-4.5	3.5-5	6-7	6-7	6-7	6-7
Fire Rating	3A/21B	5A/34B	13A/144B	21A/183B	13A	21A
Height(mm)	350	400	550	620	550	620
Width(mm)	130	140	220	230	220	230
Diameter(mm)	85	110	162	184	162	184
Working Temperature	0°C to 60°C				0°C to 60°C	
Full Weight(kg)	2.5	4.0	10.3	14.8	10.3	14.8
Bracket	Vehicle Bracket		Wall Bracket		Wall Bracket	